## MIL-LT No. 2 Heat - Shrinkable Tubing




Table 1: <u>Dimensions</u> (inches)

| As Supplied     | Recovered       |                |  |  |
|-----------------|-----------------|----------------|--|--|
| Inside Diameter | Inside Diameter | Wall Thickness |  |  |
| Minimum (D)     | Maximum (d)     | Nominal (W)    |  |  |
| .500            | .187            | .025 ± .003    |  |  |

Color: Black

**Longitudinal Change:** +0, -10%

Physical Properties: Except as specified above, MIL-LT No. 2 shall meet all the requirements of

RT-1171.

|   |                          |            |                            | Specification                                | n Control Drawing |
|---|--------------------------|------------|----------------------------|--|-------------------|
| <b>tyco</b> Electronics   | 300 Constitutional Drive |            | Raychem                    | Title: MIL-LT No. 2 Heat - Shrinkable Tubing |                   |
| Tyco Electronics reserves the right to amend this drawing at any time. Users should evaluate the suitability of the product for their application |                          |            | Document No : MIL-LT No. 2 |  |                   |
| Cage Code:<br>06090   | Scale:<br>None           | Size:<br>A | Rev. Date:<br>11-Nov-97    | Rev.:<br><b>None</b>                         | Sheet:<br>1 of 1  |